



Themec Company, Inc.
 123 West 23rd Avenue, Kansas City, MO 64116-3064
 Emergency Telephone: 800-535-5053 (INFOTRAC)
 Telephone: 816-474-3400

Material Safety Data Sheet (MSDS)

For coatings, resins and related materials, approved by the U.S. Department of Labor as essentially similar to form OSHA-20, meets requirements of CFR 29 Part 1910.1200, OSHA'S hazard communication standard. NPCA 1-84

PREPARED DATE: 09/08/2003 Series: C660-NOPG Product Class: MODIFIED POLYSILOXANE PRIME A PELL 200 Page 1 of 2

SECTION 2 - HAZARDOUS INGREDIENTS

INGREDIENTS	CAS#	% By Wt.	VAPOR PRESS. MMHG @ 68 °F	OCCUPATIONAL EXPOSURE LIMITS					
				ACGIH			OSHA		
				TLV - TWA	TLV - STEL	TLV - C	PEL - TWA	PEL - STEL	PEL - C
SILICONE RESIN SOLUTION		6-10							
ALIPHATIC HYDROCARBON MIXTURE	8052-41-3	>90		0100.000 PPM			0100.000 PPM		

** SARA Reportable Product

This product contains no reported carcinogens or suspected carcinogens. The information contained in this section is considered confidential and proprietary and should be used only for safety and health purposes.

SECTION 3 - HEALTH HAZARD INFORMATION

EMERGENCY OVERVIEW: POTENTIAL HEALTH EFFECTS: EYE: Moderate irritation. Redness, tearing, blurred vision. SKIN: Moderate irritation, drying of skin, defatting and possible dermatitis. INHALATION - OVEREXPOSURE TO SOLVENT VAPORS OR SPRAY MIST: Nasal and respiratory irritation, anesthetic effects, dizziness, possible unconsciousness and asphyxiation, stupor, weakness, fatigue, nausea, and headache. INHALATION - OVEREXPOSURE TO FREE PIGMENT DUST: INGESTION: Gastrointestinal irritation, nausea, vomiting, diarrhea, death, aspiration into the lungs which can be fatal. CHRONIC EFFECTS: NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal. TARGET ORGANS: Can cause eye irritation. Can cause skin irritation. Can cause respiratory tract irritation. Can cause nervous system effects. OTHER: This product when mixed with other components acquires the hazards of all components. PRIMARY ROUTES OF ENTRY: Dermal and Inhalation. PROPOSITION 65: Pigments and/or other raw materials present in this product contain trace amounts of a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT: Flush immediately with large amounts of clean water under low pressure for at least 15 minutes. Consult a physician. SKIN CONTACT: Wash affected area with soap and water. Remove contaminated clothing. Dispose of or launder accordingly. Consult a physician if skin irritation persists. INHALATION: Remove affected individual to fresh air. Treat symptomatically. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Consult a physician. INGESTION: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center IMMEDIATELY. Treat symptomatically. NOTE TO PHYSICIAN:

SECTION 5 - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION	FLASHPOINT	EXPLOSION LEVEL LOW	EXPLOSION LEVEL HIGH	FLAMMABILITY LIMITS LOWER	FLAMMABILITY LIMITS HIGHER
	102.0 °F	-N/A	-N/A	-N/A	-N/A

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical, water spray. FIRE-FIGHTING PROCEDURES AND EQUIPMENTS: Keep away from heat, open flames, sparks, and areas where static charge may be generated. Do not apply to hot surfaces due to possible fire and explosion risk. For closed containers, pressure build-up and possible explosion might occur due to extreme heat exposure. Solvent vapors are heavier than air and may travel considerable distance to a source of ignition and flash back. Water may be used to cool unruptured containers. Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode to prevent inhalation of hazardous decomposition products. Use appropriate extinguishing media to control fire. Water may cause violent frothing if sprayed directly into containers of burning liquid.

SECTION 6 - SPILL OR LEAK PROCEDURES

CLEAN-UP: Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal.

