

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2005

Reviewed on 01/02/2005

## 1 Identification of substance

- **Product details**

- **Trade name:** Super Seal Gray

- **Article number:** 83-300099

- **Application of the substance / the preparation**

- **Manufacturer/Supplier:**

Conspec

4226 Kansas Avenue

Kansas City, KS 66106

Tel.: (877) 266-7732

*Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.*

- **Information department:** Environmental, Health, and Safety department.

## 2 Composition/Data on components

- **Chemical characterization**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

8052-41-3	Stoddard solvent	10-25%
95-63-6	1,2,4-trimethylbenzene	10-25%
64742-95-6	Solvent naphtha (petroleum), light arom.	10-25%
108-65-6	2-methoxy-1-methylethyl acetate	£ 2.5%
1330-20-7	xylene	£ 2.5%
64742-88-7	Solvent naphtha (petroleum), medium aliph.	£ 2.5%
25551-13-7	Trimethylbenzene	£ 2.5%
108-67-8	mesitylene	£ 2.5%
98-82-8	cumene	£ 1%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

## 3 Hazards identification

- **Hazard description:** Not applicable.

- **Information pertaining to particular dangers for man and environment:**

*The product has to be labelled due to internationally acknowledged calculation procedures using the latest valid versions.*

- **Classification system:**

*The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.*

- **NFPA ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

(Contd. on page 2)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2005

Reviewed on 01/02/2005

Trade name: Super Seal Gray

(Contd. of page 1)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	2
FIRE	3
PHYSICAL HAZARD	0

Health = \*2

Fire = 3

Reactivity = 0

## 4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**  
Immediately wash with water and soap and rinse thoroughly.  
If skin irritation continues, consult a doctor.
- **After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

## 5 Fire fighting measures

- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**  
Water  
Water with full jet
- **Protective equipment:**  
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

## 6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

## 7 Handling and storage

- **Handling:**
- **Information for safe handling:**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

(Contd. on page 3)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2005

Reviewed on 01/02/2005

Trade name: Super Seal Gray

(Contd. of page 2)

Keep respiratory protective device available.

- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

## 8 Exposure controls and personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

- **Components with limit values that require monitoring at the workplace:**

### 8052-41-3 Stoddard solvent

PEL ()	2900 mg/m <sup>3</sup> , 500 ppm
REL ()	Short-term value: C 1800* mg/m <sup>3</sup> Long-term value: 350 mg/m <sup>3</sup> *15-min
TLV ()	525 mg/m <sup>3</sup> , 100 ppm

### 95-63-6 1,2,4-trimethylbenzene

REL ()	125 mg/m <sup>3</sup> , 25 ppm
TLV ()	123 mg/m <sup>3</sup> , 25 ppm

### 1330-20-7 xylene

PEL ()	435 mg/m <sup>3</sup> , 100 ppm
REL ()	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm (o-, m-, & p-isomers)
TLV ()	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI

### 25551-13-7 Trimethylbenzene

REL ()	125 mg/m <sup>3</sup> , 25 ppm (1,2,3-; 1,2,4-; and 1,3,5-isomers)
--------	---

### 108-67-8 mesitylene

REL ()	125 mg/m <sup>3</sup> , 25 ppm
TLV ()	123 mg/m <sup>3</sup> , 25 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes.  
Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 4)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2005

Reviewed on 01/02/2005

Trade name: Super Seal Gray

(Contd. of page 3)

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
 Due to missing tests, no recommendation to the glove material can be given for the product.  
 Select the glove material upon consideration of the penetration times, rates of diffusion and the degradation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

## 9 Physical and chemical properties

· **General Information**

<b>Form:</b>	Fluid
<b>Color:</b>	According to product specification
<b>Odor:</b>	Characteristic

· **Change in condition**

**Melting point/Melting range:** Undetermined.  
**Boiling point/Boiling range:** 138°C (280°F)

· **Flash point:** 37°C (99°F)· **Ignition temperature:** 230.0°C (446°F)· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

<b>Lower:</b>	0.7 Vol %
<b>Upper:</b>	7.5 Vol %

· **Vapor pressure at 20°C (68°F):** 5.0 hPa (4 mm Hg)· **Density at 20°C (68°F):** 0.94 g/cm<sup>3</sup>· **Solubility in / Miscibility with**

<b>Water:</b>	Not miscible or difficult to mix.
---------------	-----------------------------------

(Contd. on page 5)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2005

Reviewed on 01/02/2005

Trade name: Super Seal Gray

(Contd. of page 4)

- |   |        |
|---|--------|
| <b>· Solvent content:</b>                           |        |
| <b>Organic solvents:</b>                            | 35.2 % |
| <b>· Solids content:</b>                            |        |
|   | 27.6 % |
| <b>· Volatile Organic Compounds:</b> Not determined |        |

## 10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous products of decomposition:** No dangerous decomposition products known.

## 11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**95-63-6 1,2,4-trimethylbenzene**

Oral	LD50	5000 mg/kg (rat)
------	------	------------------

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

· **Primary irritant effect:**

- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
Carcinogenic.

## 12 Ecological information

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **General notes:**

Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms

USA

(Contd. on page 6)

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2005

Reviewed on 01/02/2005

Trade name: Super Seal Gray

(Contd. of page 5)

## 13 Disposal considerations

- **Product:**
- **Recommendation:** Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

## 14 Transport information

### · DOT regulations:



- **Hazard class:** 3
- **Identification number:** UN1268
- **Packing group:** III
- **Proper shipping name (technical name):** PETROLEUM DISTILLATES, N.O.S.
- **Label:** 3
- **Limited Quantity Exemption:** Limited Quantity applies for inner packages 1.3 gallons or smaller.
- **U.S. Domestic Ground Shipments:** Same as listed for Standard Shipments above.
- **U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:** Same as listed for Standard Shipments above.
- **Emergency Response Guide (ERG) Number:** Not determined

### · Land transport ADR/RID (cross-border):



- **ADR/RID class:** 3 Flammable liquids
- **Danger code (Kemler):** 30
- **UN-Number:** 1268
- **Packaging group:** III
- **Description of goods:** 1268 PETROLEUM DISTILLATES, N.O.S. (TURPENTINE SUBSTITUTE, 1,2,4-trimethylbenzene)

### · Maritime transport IMDG:



- **IMDG Class:** 3
- **UN Number:** 1268
- **Label:** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No

(Contd. on page 7)

USA

# Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2005

Reviewed on 01/02/2005

Trade name: Super Seal Gray

(Contd. of page 6)

· **Propper shipping name:** PETROLEUM DISTILLATES, N.O.S.

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3  
 · **UN/ID Number:** 1268  
 · **Label:** 3  
 · **Packaging group:** III  
 · **Propper shipping name:** PETROLEUM DISTILLATES, N.O.S.

## 15 Regulations

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

95-63-6	1,2,4-trimethylbenzene	10-25%
1330-20-7	xylene	£2.5%
98-82-8	cumene	£1%
100-41-4	ethylbenzene	£1%
108-88-3	toluene	£0.01%
7439-92-1	lead	£0.01%

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

64742-95-6	Solvent naphtha (petroleum), light arom.
14808-60-7	Quartz (SiO <sub>2</sub> )
1333-86-4	Carbon black

· **Chemicals known to the State of California (Prop. 65) to cause reproductive toxicity:**

108-88-3	toluene
----------	---------

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	D
98-82-8	cumene	D; CBD
100-41-4	ethylbenzene	D
108-88-3	toluene	D

(Contd. on page 8)

**Material Safety Data Sheet**  
acc. to ISO/DIS 11014

Printing date 01/02/2005

Reviewed on 01/02/2005

Trade name: Super Seal Gray

(Contd. of page 7)

7439-92-1	lead	B2
<b>· IARC (International Agency for Research on Cancer)</b>		
1330-20-7	xylene	3
100-41-4	ethylbenzene	2B
14808-60-7	Quartz (SiO <sub>2</sub> )	1
14464-46-1	crystalite	1
108-88-3	toluene	3
7439-92-1	lead	2B
1333-82-0	chromium (VI) trioxide	1
1333-86-4	Carbon black	2B
<b>· NTP (National Toxicology Program)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	K
14464-46-1	crystalite	K
1333-82-0	chromium (VI) trioxide	K
<b>· TLV (Threshold Limit Value established by ACGIH)</b>		
1330-20-7	xylene	A4
14808-60-7	Quartz (SiO <sub>2</sub> )	A2
108-88-3	toluene	A4
7439-92-1	lead	A3
1333-86-4	Carbon black	A4
<b>· MAK (German Maximum Workplace Concentration)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	1
14464-46-1	crystalite	1
1333-86-4	Carbon black	3
<b>· NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
14808-60-7	Quartz (SiO <sub>2</sub> )	
14464-46-1	crystalite	
1333-86-4	Carbon black	
<b>· OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

**· Product related hazard informations:**

The product has been classified and marked in accordance with directives on hazardous materials.

**· Hazard symbols:**

T Toxic

N Dangerous for the environment

**· Hazard-determining components of labelling:**

Stoddard solvent

Solvent naphtha (petroleum), light arom.

(Contd. on page 9)

USA



## Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2005

Reviewed on 01/02/2005

**Trade name: Super Seal Gray**

(Contd. of page 8)

· **Risk phrases:**

- 45 *May cause cancer.*
- 10 *Flammable.*
- 36/37 *Irritating to eyes and respiratory system.*
- 51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*
- 65 *Harmful: may cause lung damage if swallowed.*

· **Safety phrases:**

- 53 *Avoid exposure - obtain special instructions before use.*
- 2 *Keep out of the reach of children.*
- 9 *Keep container in a well-ventilated place.*
- 13 *Keep away from food, drink and animal feedingstuffs.*
- 16 *Keep away from sources of ignition - No smoking.*
- 20 *When using do not eat or drink.*
- 23 *Do not breathe fumes/aerosol.*
- 24/25 *Avoid contact with skin and eyes.*
- 26 *In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.*
- 28 *After contact with skin, wash immediately with plenty of soap and water.*
- 29/56 *Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.*
- 33 *Take precautionary measures against static discharges.*
- 36/39 *Wear suitable protective clothing and eye/face protection.*
- 43 *In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.*
- 45 *In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).*
- 57 *Use appropriate container to avoid environmental contamination.*
- 64 *If swallowed, rinse mouth with water (only if the person is conscious).*

· **National regulations:**

- **Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.

### 16 Other information

*The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

- **Department issuing MSDS:** Environmental, Health & Safety Department
- **Contact:** Environmental, Health & Safety Manager