Page 1

Date of preparation: 01/06/06 3016000

SECTION I

Manufacturer : W. R. MEADOWS, INC. - H M I S -

Address : 300 Industrial Drive | Health : 1 | : Hampshire, IL 60140 | Flammability : 0 |

|Reactivity : 0 |

Telephone # : (847) 683-4500 | Personal Protection : |

Emergency # : 1-800-424-9300 Chemtrec

(Hazard Rating: 0=Least,1=Slight,2=Moderate,3=High,4=Extreme,*=Chronic)

Product Class : DIVISION 3
Mfg. code I.D. : 3016000

Trade Name : 1600 WHITE WAX WATER BASE CURING COMPOUND

SECTION II-A HAZARDOUS COMPONENTS

LEL % by SARA VAPOR PRESSURE CAS# Weight 313 (mm Hg @ 20 C) (@ 25 C) No. Component 1. Titanium Dioxide 13463-67-7 1-5 NO N/A N/A

None of the components of this product are recognized as carcinogenic. N/A = Not Applicable

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313".

SECTION II-B OCCUPATIONAL EXPOSURE LIMITS

OSHA ACGIH No. PEL/TWA PEL/CEILING PEL/STEL SKIN TLV/TWA TLV/CEILING TLV/STEL SKIN 1. N/E N/E 10 ma/m³+ N/E N/E 15 mg/m3* N/F N/F N/E = Not established * = Total Dust + = 5mg/m3 Respirable fraction

SECTION III PHYSICAL DATA

Boiling Point: 212 degrees F% Volatile by volume: 74.88 (Theoretical)Evaporation Rate: <1 (ether = 1)</th>% Volatile by weight: 75.56 (Theoretical)Vapor Density: > 1 (air = 1)Weight per gallon: 8.25 (Theoretical)pH Level: 8.67

SECTION IV HEALTH INFORMATION

EYE CONTACT: Direct contact may result in mild eye irritation. **SKIN CONTACT:** Direct contact may result in mild skin irritation.

INHALATION: Exposure may produce irritation to the nose, throat, respiratory tract and other mucous membranes.

INGESTION: May cause irritation of the gastrointestinal tract.

SIGNS AND SYMPTOMS: Symptoms of eye irritation include pain, tearing, reddening, and swelling. Symptoms of skin irritation include reddening, swelling, rash, and redness. Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and reduced lung function. Symptoms of gastrointestinal irritation include sore throat, abdominal pain, nausea, vomiting, and diarrhea.

AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to this product.

OTHER HEALTH EFFECTS: Chronic overexposure to Titanium Dioxide dust may cause slight lung fibrosis.

SECTION V EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Immediately flush eyes with copious amounts of water for at least fifteen (15) minutes while holding eyelids open. Seek prompt medical attention.

SKIN CONTACT: Remove contaminated shoes and clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists seek medical attention.

INHALATION: If respiratory symptoms develop, move victim away from exposure source and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

INGESTION: Dilute with liquid unless the victim is unconscious or very drowsy. If vomiting spontaneously occurs, keep the victim's head below the hips to prevent aspiration into the lungs. Consult a physician, hospital, or poison control center and/or transport to an emergency facility immediately.

Date of preparation: 01/06/06 3016000

Page 2 3016000

Date of preparation: 01/06/06

SECTION VI

FIRE AND EXPLOSION HAZARDS

FLAMMABILITY CLASSIFICATION

- NFPA: Combustible Liquid - Class IIIB

- DOT: Not Regulated

FLASH POINT: Greater than 210 degrees F

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical or Carbon Dioxide **SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:** None recognized.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None recognized.

SECTION VII

REACTIVITY

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS AND MATERIALS TO AVOID: None recognized

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield Carbon Dioxide, Carbon Monoxide, and/or incomplete combustion products. Do not breathe smoke or fumes. Wear appropriate protective equipment.

SECTION VIII

EMPLOYEE PROTECTION

RESPIRATORY PROTECTION: None required with normal product use.

PROTECTIVE CLOTHING: Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

ADDITIONAL PROTECTIVE MEASURES: Eye wash fountains and safety showers should be available for use in an emergency.

SECTION IX

ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES: LARGE SPILLS>> Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above. SMALL SPILLS>> Take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal.

WASTEDISPOSAL: Observe all Federal, State and local regulations regarding proper disposal.

SECTION X

ADDITIONAL PRECAUTIONS

Containers can contain product residues even when empty. Wash with soap and water before eating, drinking, smoking or using toilet facilities.

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.

Date of preparation: 01/06/06 3016000