## \*\*\* MATERIAL SAFETY DATA SHEET \*\*\*

## Date of preparation: 07/01/04

## **SECTION I**

Trade Name	: GARDOX COMPONENT B			
Mfg. code I.D.	: 401000-4			
Product Class	: DIVISION 2			
		(Hazard Rating: 0=Least,1=Slight,2=Moderate	e,3=High,4=Extreme,*=Chronic)	
Emergency #	: 1-800-424-9300 Chemtrec			
Telephone #	: (847) 683-4500	Personal Protection	:	
		Reactivity	:0	
	: Hampshire, Illinois 60140	Flammability	:1	
Address	: 300 Industrial Drive	Health	:2	
Manufacturer	: W. R. MEADOWS, INC.	- H M I S -		

#### SECTION II-A HAZARDOUS COMPONENTS

			% by	SARA	VAPOR PRI	ESSURE I	LEL
No.	Component	CAS#	Weight	313	(mm Hg @ :	20 C)	(@ 25 C)
1.	Aromatic Oil	64741-81-7	1-5	NO	N/A		N/A
2.	1,2 - Benzanthracene	56-55-3	0-1	YES	N/A		N/A
3.	Coal Tar	65996-89-6	45-50	YES	N/A		N/A
4.	Calcium Oxide	1305-78-8	1-5	NO	N/A		N/A
>> C	Component number 3 is listed by NTP a	nd IARC as a card	cinogen or a	possible card	cinogen. N	I/A= Not Applic	able

>> Component number 3 is listed by NTP and IARC as a carcinogen or a possible carcinogen.

>> Component number 2 is listed by IARC as a carcinogenic material.

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313".

#### SECTION II-B **OCCUPATIONAL EXPOSURE LIMITS**

		USHA			ACGIH			
No	). PEL/TWA	PEL/CEILING	PEL/STEL	SKIN	TLV/TWA	TLV/CEILING	TLV/STEL	SKIN
1.	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E
2.	N/E	N/E	N/E	N/E	N/E	N/E	N/E	N/E
3.	0.2 mg/m3*	N/E	N/E	N/E	0.2 mg/m3*	N/E	N/E	N/E
4.	5 mg/m3*	N/E	N/E	N/E	2 mg/m3*	N/E	N/E	N/E

Skin absorption may contribute to the overall exposure to this material. Take appropriate measures to prevent skin contact.

N/E = Not established

SECTION III	PHYSIC	AL DATA		
Boiling Point	: Not Established	% Volatile by volume	: 1.07 (Theoretical)	
Evaporation Rate	: <1 (ether = 1)	% Volatile by weight	: 0.79 (Theoretical)	
Vapor Density	: >1 (air = 1)	Weight per gallon	: 9.26 (Theoretical)	
SECTION IV	HEALTH	INFORMATION		

EYE CONTACT: Based on the presence of components 1 and 3 this product is presumed to be moderately irritating to the eyes. Exposure may cause corneal injury. Product vapors and/or mists may also be irritating to the eyes.

SKIN CONTACT: Exposure may produce mild to moderate skin irritation. Prolonged/repeated contact may result in defatting/drying of the skin which may result in dermatitis.

INHALATION: Based on the presence of components 1 and 3 overexposure to vapor may result in irritation to the respiratory tract. Prolonged/repeated exposure in significant excess of permissible air concentrations can result in acute toxic effects, such as respiratory difficulty, convulsions, and possible cardiovascular collapse.

INGESTION: Based on the presence of component 3 this product may cause irritation of the gastrointestinal tract followed by nausea, abdominal discomfort, and rapid pulse is possible. Cardiovascular collapse may occur. Fatal dose is about 0.1 g/kg of body weight.

SIGNS AND SYMPTOMS: Symptoms will vary from mild irritation to severe burning based on the concentration of the material and the duration of the exposure.

AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye and respiratory disorders may be aggravated by exposure to this product.

OTHER HEALTH EFFECTS: Based on the presence of component 1 prolonged and repeated skin exposure over many years in the absence of recommended hygiene practices may lead to changes in skin pigmentation, benign skin growths, and may, in some cases, result in skin cancer. Additionally, inhalation of vapors over a period of several years may present a lung cancer hazard. Aromatic oils are also a cancer risk depending on the amount/duration of the exposure.

### EMERGENCY AND FIRST AID PROCEDURES SECTION V

EYE CONTACT: Immediately flush eyes with copious amounts of water for fifteen (15) minutes while holding eyelids open. Seek prompt medical attention.

SKIN CONTACT: Remove contaminated shoes and clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

INHALATION: If respiratory symptoms develop, move victim away from exposure source and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

INGESTION: Dilute with two glasses of water unless the victim is unconscious or very drowsy. Induce vomiting by giving two tablespoons of Ipecac or by touching a finger to the back of the victim's throat. Keep the victim's head below the hips to prevent aspiration into the lungs. Consult a physician, hospital or poison control center and/or transport to an emergency facility immediately.

### SECTION VI FIRE AND EXPLOSION HAZARDS

FLAMMABILITY CLASSIFICATION

- NFPA: Combustible Liquid - Class IIB - DOT: Not Regulated

FLASH POINT: 250 degrees F

EXTINGUISHING MEDIA: Use water fog, foam, dry chemical, or Carbon Dioxide

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS: Clear fire area of unprotected personnel. Do not enter confined fire space without helmet, face shield, bunker coat, gloves, rubber boots, and a positive pressure NIOSH approved self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as need to prevent weakening of container structure.

## SECTION VII

## REACTIVITY

**STABILITY: Stable** 

HAZARDOUS POLYMERIZATION: Will not occur CONDITIONS AND MATERIALS TO AVOID: Avoid oxidizing materials and strong acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may yield Carbon Dioxide, Carbon Monoxide, and/or incomplete combustion products. Do not breathe smoke or fumes. Wear appropriate protective equipment.

## SECTION VIII

# EMPLOYEE PROTECTION

RESPIRATORY PROTECTION: Use ventilation as required to control vapor concentrations - at least 10 air changes per hour are recommended for good general room ventilation. If exposure exceeds the PEL/TLV, use the appropriate NIOSH approved respirator.

PROTECTIVE CLOTHING: Wear safety glasses, goggles, or a splash shield to prevent eye contact. Contact lenses should not be worn. Wear appropriate gloves and protective clothing to prevent contact with skin and clothing.

ADDITIONAL PROTECTIVE MEASURES: Eye wash fountains and safety showers should be available for use in an emergency.

### **ENVIRONMENTAL PROTECTION** SECTION IX

SPILL OR LEAK PROCEDURES: LARGE SPILLS>>Evacuate the hazard area of unprotected personnel. Wear appropriate respirator and protective clothing. Shut off source of leak only if safe to do so. Dike and contain. If vapor cloud forms, water fog may be used to suppress; contain run-off. Remove with vacuum trucks or pump to storage/salvage vessels. Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue. Dispose of flush solutions as above. SMALL SPILLS>> Take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal.

WASTE DISPOSAL: Observe all Federal, State and local regulations regarding proper disposal.

## SECTION X

# ADDITIONAL PRECAUTIONS

Containers may contain hazardous product residues even when empty. Wash with soap and water before eating, drinking, smoking or using toilet facilities.

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.